

# TECHNICAL SPECIFICATION



## PressToCheck™ A2 P3 Filters

Pack of 2 / BMN740-000-600



### DESCRIPTION

PressToCheck™ is the easiest way to face-fit check the seal of your respirator, every time you put it on! The range features HEPA filtration exceeding 99.95%, Low profile design maximising compatibility and low breathing resistance across the range.

F-4123 A2P3 organic gas / vapour + dust replacement encapsulated filters, featuring PressToCheck™ technology for daily face-fit reassurance.

Winner of the BSIF Product Innovation Award.

### OPTIONS

**Pack of 2 (BMN740-000-600)**

### SAFETY STANDARDS

EN 14387



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jspsafety.com](mailto:sales@jspsafety.com) / Web: [www.jspsafety.com](http://www.jspsafety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jspsafety.com](mailto:copyright@jspsafety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 25 Apr 2022 / Copyright 2018 - 2022. JSP Limited. All Rights Reserved.



## SPECIFICATIONS

Classification  
**A2P3**

Usage  
**R (Reusable)**



Activated Carbon Filter  
**Yes**

Maximum Total Inward Leakage (TIL)  
**2% when fitted to Force8 Half Mask**

Nominal Protection Factor  
**12 When Fitted To A Force8 Half Mask**

UK Assigned Protection Factor  
**10 When Fitted To A Force8 Half Mask**



Type  
**Press To Check Technology**

Metal Free  
**Yes**

Filter Casing Material  
**ABS**



BSI Kitemark  
**Yes**



Filter Type  
**Organic Vapours, Nuisance Odours and Particulate**



(D) Resistance to dust clogging  
**Yes – D marking = passes optional clogging test**

Minimum Filtration Efficiency  
**99.95% For P Rated**

Maximum Total Inward Leakage (TIL)  
**0.05% when fitted to a Force10 Full Face Mask**

Nominal Protection Factor  
**1000 When Fitted To A Force10 Full Face Mask**

UK Assigned Protection Factor  
**20 When Fitted To A Force10 Full Face Mask**

Latex free  
**Yes**

Filter Material  
**Pleated Media & Activated Carbon**

Filter Shelf Life  
**10 Years**



Product Weight  
**231g Per Pair**

## FEATURES



### Increased Product Life

PressToCheck™ encapsulated filters offer ultimate longevity – the durable design makes the filters easy to clean and reuse. Correct cleaning, maintenance and storage increases the useful life of the product.

## VIDEOS

- [youtu.be/1Y9G8E9kEXQ](https://youtu.be/1Y9G8E9kEXQ)
- [youtu.be/Ecyu\\_ftPPX4](https://youtu.be/Ecyu_ftPPX4)
- [youtu.be/-oUSyP9\\_NsA](https://youtu.be/-oUSyP9_NsA)

## DOWNLOADS

- [Image Pack \(ZIP\)](#)
- [doc-force-press-to-check-filter-f-4123.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: [sales@jsp-safety.com](mailto:sales@jsp-safety.com) / Web: [www.jsp-safety.com](http://www.jsp-safety.com)

Do Not Publish without written permission from JSP Limited. Contact [copyright@jsp-safety.com](mailto:copyright@jsp-safety.com). Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 25 Apr 2022 / Copyright 2018 - 2022. JSP Limited. All Rights Reserved.

