SKYTEC SAPPHIRE CARBON

MICRO-FOAM NITRILE GRIP GLOVE WITH HIGH CUT RESISTANCE

Breathable and oil resistant with excellent cut protection. No composite fibres for improved comfort and reduced risk of irritations. Ideal for precise tasks in wet or slightly oily environments with high cut risks.

FEATURES

- > Cut resistant: Level C (EN 388:2016)
- A flexible and comfortable glove offering great dexterity
- Micro-foam nitrile coating gives exceptional grip while allowing warm air and moisture from inside to escape, keeping hands dry and comfortable
- > No steel or glass fibres for reduced risk of irritation
- > Reinforced thumb crotch enhances durability
- > Designed for easy movement and continuous wear
- > Breathable back of hand to reduce perspiration
- > Seamless knit prevents irritation
- > Elasticated wrist provides a secure fit





SUITABLE FOR

Typical Industries

- Automotive
- Construction
- Maintenance
- Manufacturing
- Logistics

Suitable Applications

- Assembling
- Handling sharp and oily parts
- Machining
- Glass Handling
- Bodywork

CERTIFICATION





EN 388:2016

4X42C



See overleaf for explanation



SKYTEC[®] SAPPHIRE CARBON

PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge HPPE, nylon
	COATING:	Micro foam nitrile
COLOUR	Grey (red cuff)/Black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKY00071 SKY00072 SKY00073 SKY00074 SKY00075	10 pairs per bag 120 pairs per case

RECOMMENDATIONS FOR USE

- USE: General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS* 0-4 0-5 0-4 0-4 A-F P

> Limpact Resistance Straight Blade Cut Resistance (EN ISO: 13997) Puncture Resistance Tear Resistance Circular Blade Cut Resistance

Abrasion Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- **T:** +971 4 882 9962
- F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



©2021 Globus (Shetland) Ltd | SKY-DATA-SAPP-CARBON-0420_1

EU Type-Examination Certificate issued by SATRA Technology Centre, Wyndham Way, Telford Way, Kettering, Northamptonshire, NN16 8SD, United Kingdom (Notified Body No. 0321) The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.