sноша. **377-IP**

LIGHT IMPACT PROTECTION, FLEXIBILITY AND OUTSTANDING OIL GRIP

Fully coated nitrile with an additional coating of foam nitrile to the palm. The SHOWA-configured Thermo Plastic Rubber (TPR) protection shields to the back of the fingers and hand are designed to bolster protection against crushes and light impacts.

FEATURES

- > Helps protect the hand from oils, hydrocarbons, grease and abrasion
- SHOWA patented nitrile foam coating provides excellent grip in wet and greasy conditions
- > Flexible and durable TPR shields provide light impact protection to the back of the hand
- > Extremely flexible
- > Robust and durable
- > Reinforced knit cuff



Flexible and Durable TPR Shields

SUITABLE FOR

Typical Industries

DUAL COATING TECHNOLOGY

Airports

OIL SUBMERSION

- Heavy Construction
- Mining
- Offshore
- Oil and Gas
- Ports

Suitable Applications

VENDING MACHINE

- Cargo Handling
- Demolition
- Drilling

OIL GRIP

- Engineering
- Extraction and Refining
- Operating Machinery
- Rigging


CERTIFICATION





See overleaf for explanation







PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge nylon, polyester
	COATING:	Foam nitrile over nitrile
COLOUR	White/blue and black	
LENGTH (mm)	250 (size dependent)	
CUFF STYLE	Elasticated knit wrist	

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/M 8/L 9/XL 10/XXL	SHO377IP2 SHO377IP3 SHO377IP4 SHO377IP5	5 pairs per bag 60 pairs per case

RECOMMENDATIONS FOR USE

- USE: General handling glove with light impact protection. Not suitable for thermal, electrical or chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS* 0-4 0-5 0-4 0-4 A-F P

Straight Blade Cut Resistance (EN ISO: 13997) Puncture Resistance Tear Resistance Circular Blade Cut Resistance

Abrasion Resistance

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globusgroup.com

- E: sales@globus.co.uk
- T: +44 (0)161 877 4747
- F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

- E: gcc@globusgroup.com
- **T:** +971 4 882 9962
- F: +971 4 882 9963

Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES



©2020 Globus (Shetland) Ltd | SHO-DATA-377-IP_0620_1

EU compliance certificate delivered by the notified body SGS Fimko Oy, Särkiniementie 3, Helsinki, 00211, Finland (Notified Body number 0598)

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary