



CHEMICAL RESISTANT HEAVY-DUTY FLOCK-LINED NATURAL RUBBER GLOVE

Nero provides mechanical protection as well as resistance from chemicals and cleaning fluids. The pattern on the palm provides grip in slippery and dry handling conditions.

FEATURES

- > Heavy-duty for enhanced protection
- > Anti-slip hexagon grip design to palm and fingertips
- > Resistance to water-based chemicals
- > Bacteriostatic and fungistatic additives
- > Pure cotton flock lining absorbs perspiration
- Chlorinated surface
- > Thickness: 0.65mm for a supple wearing experience
- **)** Low in soluble proteins
- Anatomically-shaped to minimise hand fatigue







SUITABLE FOR

Typical Industries

- Agriculture
- Bio-pharmaceutical
- Chemical Processing
- Construction
- Engineering
- Manufacturing
- Utilities

Suitable Applications

- Chemical Handling
- Cleaning
- HGV Drivers
- Maintenance of Equipment
- Medical Research

CERTIFICATION

CAT III EN 388:2016



2020X

EN ISO 374-1:2016/Type A

AKLMNPST

See overleaf for explanation







PRODUCT INFORMATION LINER: Cotton Flock COATING: Natural latex COLOUR Black LENGTH (mm) 300

ORDERING DETAILS

CUFF STYLE

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL	SKY871 SKY872 SKY873 SKY874	10 pairs per bag 120 pairs per case

RECOMMENDATIONS FOR USE

- USE: Chemical resistant glove. Not suitable for thermal, electrical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from direct sunlight
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use

PROTECTION AGAINST

MICRO-ORGANISMS EN 374-5 VIRUS = Glove has passed ISO 16604: 2004 (method B)


WARNING: Latex may cause allergies

CERTIFICATION LEGENDS



MECHANICAL HAZARDS EN 388:2016 PERFORMANCE LEVELS*

Gauntlet



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL
A	Methanol	J	n-Heptane
В	Acetone	K	Sodium hydroxide 40%
C	Acetonitrile	L	Sulphuric acid 96%
D	Dichloromethane	M	65% Nitric acid
E	Carbon Disulfide	N	99% Acetic acid
F	Toluene	0	25% Ammonium hydroxid
G	Diethylamine	P	30% Hydrogen peroxide
Н	Tetrahydrofurane	S	40% Hydrofluoric acid
I.	Ethyl acetate	T	37% Formaldehyde

TYPE OF GLOVES	BREAKTHROUGH TIME
Α	≥30 min for at least 6 chemicals
В	≥30 min for at least 3 chemicals
С	≥10 min for at least 1 chemical

EUROPE

www.globusgroup.com

E: sales@globus.co.uk T: +44 (0)161 877 4747 F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com T: +971 4 882 9962 F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2021 Globus (Shetland) Ltd | SKY-DATA-NERO-0420_1