



CUT RESISTANT, THERMAL, WATER REPELLENT FULLY COATED LATEX GLOVE

A fully coated glove combining thermal properties and cut resistance with an open cuff for easy donning and doffing. Ideal for sharp handling in cold and wet environments.

FEATURES

- > Cut resistant: Level D (EN 388:2016)
- Cut resistant liner protects against sharp parts and the thermal liner provides insulation at cold temperatures
- > Flexible and robust glove offering a good level of dexterity
- > Water repellent for working in wet environments
- Protects the hand from liquids with optimal long lasting grip
- Open cuff (cut-out in wrist area) to ease removal of the glove
- > No irritation by seams in contact with the skin





SUITABLE FOR

Typical Industries


- Construction
- Glass
- Public Works
- Transportation
- Waste Management

Suitable Applications

- Sharp and Wet Parts Handling
- Scaffolding

CAT II EN 388:2016 EN 511:2006 See overleaf for explanation







SKYTEC RADIUS EW151

PRODUCT INFORMATION

MATERIALS	LINER:	13 gauge HPPE, glass fibre, nylon, acrylic	
	COATING:	Double coated crinkle latex over latex	
COLOUR	Grey/Black		
LENGTH (mm)	250 (size dependent)		
CUFF STYLE	Open cuff		

ORDERING DETAILS

SIZE	CODE	PACKAGING
7/S 8/M 9/L 10/XL 11/XXL	SKY00131 SKY00132 SKY00133 SKY00134 SKY00135	10 pairs per bag 60 pairs per case

RECOMMENDATIONS FOR USE

- USE: Cold and cut resistant glove. Not suitable for thermal (heat), electrical
 or chemical protection. Do not use near moving machines if there is a risk of entanglement
- STORAGE: Store in dry conditions in the original packaging and away from
- CLEANING: To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- LIFETIME: Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use
- WARNING: Latex may cause allergies

CERTIFICATION LEGENDS



*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter



COLD HAZARDS EN 511

PERFORMANCE LEVELS 0-5 0 or 1 Water Permeability Contact Cold Resistance Convective Cold Resistance

EUROPE

www.globusgroup.com

E: sales@globus.co.uk +44 (0)161 877 4747 +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com +971 4 882 9962 F: +971 4 882 9963



Globus Group, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2021 Globus (Shetland) Ltd | SKY-DATA-RAD-EW151-0420_1