

SINGLE-USE GLOVE, 100% NITRILE, POWDER-FREE, SILICONE-FREE, 300MM LONG, 0.20MM THICK

Premium performance, powder-free, extended cuff, nitrile, single-use glove. Extremely strong and high resistance to chemicals.

FEATURES

- › High-quality nitrile, soft and durable
- › High resistance to penetration and projections of many chemicals
- › Palm thickness 0.20mm (8 mil), weight: 9.2g, size M
- › Extended cuff (300mm length) to protect the forearm
- › Textured finish on palm to enhance grip
- › Powder-free, latex-free, non-sterile
- › Chlorinated inside to offer increased comfort and reduce friction when donning
- › AQL 0.65
- › Anti-static properties due to inherent anti-static properties of nitrile
- › Silicone-free



SUITABLE FOR

Typical Industries

- Chemicals
- Electronics
- Manufacturing
- Oil and Gas
- Pharmaceutical
- Repair and Finishing

Suitable Applications

- Chemical Handling
- Handling Oily Components
- Laboratory Analysis
- Light Assembly
- Paint Spraying

CERTIFICATION

CAT III
**UK
 CA**
 0120

EN ISO 374-1:2016/Type B

 JKOPT

EN ISO 374-5:2016

See overleaf for explanation

PRODUCT INFORMATION		
MATERIALS	LINER:	Nitrile
	COATING:	N/A
COLOUR	Blue	
LENGTH (mm)	300 mm	
CUFF STYLE	Beaded	

- ### RECOMMENDATIONS FOR USE
- **USE:** Single use glove. Not suitable for Mechanical, thermal, heat, electrical, heavy chemical protection. Do not use near moving machines if there is a risk of entanglement.
 - **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight.
 - **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
 - **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	SKG00830DB	50 singles per box
7/S	SKG00830DD	
8/M	SKG00830DF	10 boxes per case
9/L	SKG00830DH	
10/XL	SKG00830DJ	
11/XXL	SKG00830DL	

CERTIFICATION LEGENDS

RESISTANCE TO CHEMICAL PERMEATION - EN ISO 374:2016

CODE	CHEMICAL	CODE	CHEMICAL	TYPE OF GLOVES	BREAKTHROUGH TIME
A	Methanol	J	n-Heptane	A	≥30 min for at least 6 chemicals
B	Acetone	K	Sodium hydroxide 40%		
C	Acetonitrile	L	Sulphuric acid 96%		
D	Dichloromethane	M	65% Nitric acid		
E	Carbon Disulfide	N	99% Acetic acid		
F	Toluene	O	25% Ammonium hydroxide		
G	Diethylamine	P	30% Hydrogen peroxide	B	≥30 min for at least 3 chemicals
H	Tetrahydrofurane	S	40% Hydrofluoric acid		
I	Ethyl acetate	T	37% Formaldehyde		

PROTECTION AGAINST MICRO-ORGANISMS EN 374-5

VIRUS = Glove has passed ISO 16604:2004 (method B)

EUROPE
www.globusgroup.com
E: sales@globus.co.uk
T: +44 (0)161 877 4747
F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA
www.globusgroup.com/gcc
E: gcc@globusgroup.com
T: +971 4 882 9962
F: +971 4 882 9963

